

HT-8336 TLP

High Precision Load Cell

直式荷重元



HT-8336 LTP Load cell

R320 Indicator



Weight Smart

- Durable IP65 ABS panel mount housing
- Durability maximised with the protective lens over the LCD to reduce risk of damage from knocks
- Optional desk stand with non-slip rubber feet Stainless steel swivel bracket for pole or wall mounting
- 4 AA Battery compartment built into optional desk stand

Capacity (kN)	1000kN / 2000kN
Output	2.0001 mv/v
Zero	< 2 % of Full Scale
Creep (30 min)	< 0.1% of Full Scale
Non-Linearity	<0.1% of Full Scale
Hysteresis	<0.1% of Full Scale
Repeatability	<0.1% of Full Scale
Temperature effect on Output	< 20 ppm/°C of Applied Load
Temperature effect on Zero	< 20 ppm/°C of Applied Load
Operating Temperature Range	-40°C to 80°C
Compensated Temperature Range	-10°C to 40°C
Safe Overload	1.5 x Capacity
Input Resistance	350 ± 5 ohms
Output Resistance	350 ± 3 ohms
Insulation Resistance	≥ 5000 Meg-ohme
Recommended Excitation	10VDC/AC
Maximum Excitation	20VDC/AC

==== Thank you for choosing Hung Ta as your Testing needs! =====www.hungta.com=====